

Certified High Flex Camera Link - Straight - CLCP-XX-P

Product Outline

These molded InterFlex assemblies are Certified to Camera Link Committee Standards.

By combining the most advanced materials and sophisticated building techniques Intercon 1 provides the most robust industrial assemblies available. These assemblies are designed to function within a broad range of temperature and environmental conditions and may be used in either static or flex applications.

Intercon 1 high-flex cable construction adheres with the Camera Link specifications and performs past 1 million flex cycles.



Main Product Specifications

Features

- ▶ Overmolded
- ▶ Thumbscrew locking
- ▶ Designed to surpass 1 million flex cycles
- ▶ RoHS Compliant
- ▶ Camera Link Certified

Cable Specifications

Overall Diameter	.375 inches
Max Temperature	80 degrees Celsius
Jacket Color	Black
UL/CSA Rated	Yes
Min. Bend Radius	3.75 inches
Flame Rating	FT-1

Primary Components

Cable	11 Individually Shielded Twisted Pairs
Connector A	26 Pos MDR
Connector B	26 Pos MDR

Ordering Information

Order No.	Length		Description
	Meters	Feet	
CLCP-1.0-P	1.0	3.28	High Flex Camera Link
CLCP-2.0-P	2.0	6.56	High Flex Camera Link
CLCP-3.0-P	3.0	9.84	High Flex Camera Link
CLCP-4.5-P	4.5	14.76	High Flex Camera Link
CLCP-5.0-P	5.0	16.4	High Flex Camera Link

Custom variations are available. Please contact customer service for additional information.

A division of Nortech Systems, Inc - 7746 Goedderz Road Suite 110 - Baxter, MN 56425
 P: 800.237.9576 - F: 218.828.1096 - intercon@nortechsys.com - www.intercon-1.com